BSLBATT®
Best Solution Lithium Battery

Floor Cleaning Machine LiFePO4Battery

B-LFP24-205FM



MODEL B-LFP24-205FM
NOMINAL VOLTAGE 25.6V
NOMINAL CAPACITY 205Ah
CELL CHEMISTRY Lithium Iron Phosphate (LiFePO4)
CYCLE LIFE ≥4000 cycles at 25℃, 0.5C rate, 80% DOD to 80% of initial capacity

SAFETY & INTELLIGENCE
- Continuous voltage, current, and temperature monitoring
- Six redundant safety protections using Level 4 fuses.
- Multiple battery isconnects and Microprocessors
- CAN-Bus Communication
- SOC can check the power at any time
- Bluetooth@ (MOS solution)

PHYSICAL SPECIFICATIONS

Dimensions L*W*H Inches (MM)	21.26*12.99*10.83 (540*330*275)
Weight (KG)	47
Terminal Type	M8
Protection Level	IP65
Shell Material	iron
Handle Material	Metal
Calendar Life	12years 25℃，SOC 100% ,EOL 80%
Battery pack factory SOC	50%
Battery SOC operating range	0-100%

ELECTRICAL SPECIFICATIONS

Nominal Voltage (V)	25.6
Operating Voltage	20V to 29.2V Battery Cell:2.5 ~3.65
Capacity AMP Hours (AH)	205Ah
Energy (WH)	5,248 Wh
Self-Discharge	1-3% per month
Battery Group Solution	8S1P A boxful

TEMPERATURE SPECIFICATIONS

Discharge Temperature Range	-4°F to 140°F (-20℃ to 60℃)
Charge Temperature Range	32°F to 131°F (0℃ to 55℃)
Storage Temperature Range	-4°F to 140°F (-20℃ to 60℃)

PHYSICAL PRECISION

Insulation requirements	≥20MΩ/1000VDC 25℃±5℃ RH50%
Unit voltage acquisition accuracy	±5mV Capture every single monomer
Balanced current	30mA ±10 passive balance
BMS power consumption	≤3W
Temperature acquisition accuracy	±2℃
SOC theoretical estimation accuracy	±5%
Current acquisition accuracy	≤ ± 0.5% FSR

SAFETY AND FEATURES

Protection function	Short Cicuit Protection Overheat Protection Overcharge Protection	Over-discharge Protection Overcurrent Protection Real-time Temperature Monitoring
Battery Insurance	PICC	
Battery case function	Switch sleep button Pressure relief valve	
Battery certification	UL/CE/IEC/UN38.3	

DISCHARGE SPECIFICATIONS Perormance and System @77°F (25℃)

Maximum Continuous Discharge Current	102A
Maximum Pulse Discharge Current (10 sec)	205A

CHARGING SPECIFICATIONS

Recommended Standard Charger Current	≤60A
Maximum Continuous Charging Current	102.5A50°F~113°F (10℃~45℃), 5% < SOC < 80%
Maximum instantaneous charging current (1S)	153A 50°F~113°F (10℃~45℃), 5% < SOC < 80%

www.lithium-battery-factory.com / www.bslbatt.com

Designed and finally processed by China
BSLBATT Battery Company, the batteries are manufactured in China.

All data based on the BSLBATT standard test procedure on a flat road